




STF: for components packaged in sticks and needing cutting, bending or forming







FEATURES

- For components packaged into plastic sticks and which pins need:
 - cutting
 - and / or bending and / or forming
- Ability to perform up to three of these processes in the same feeder

BENEFITS

- Use of standard components from electronic supplier
- No need for additional off-line machine to preform
- Component traceability (managed by pick-and-place machine)
- All the benefits of the field proven SEMO tube feeder

Width: 90 mm

Length: 1320 (810 outside

table)

Weight: 27 kg

Power supply: 110/220 Vac -

50/60 Hz

Air supply: 5 / 7 bar



DID YOU KNOW?

What to do when your component is discontinued? **SEMO Feeders can be recycled**

We can reconfigurate to new components, test, upgrade and provide the new full warranty: a new life for your feeder and some savings for you.





INTEGRATION WITH PICK-AND-PLACE MACHINES

- Possible integration with many pick-and-place machines
- SEMO feeders can communicate with pick-and-place machines or can function manually for tests and maintenance.

CHARACTERISTICS

- Automatic startup with cycle time < 2s
- Lengths of sticks: 500 mm to 600 mm maximum
- Gravity system: sticks tilted to 45°
- Number of sticks depends on the sticks height: storage stick height 250 mm
- Stick replenishment without stopping production
- Repeatability of positionning: < 0.1 mm
- SEMO Tube Feeder can be mounted on a changeover table every 80 mm
- Optional communication for optimal synchronization with pick and place machine
- A mobile crutch supports the feeders weight once mounted on a placement machine
- Reconfigurable if you need to convert your feeder to another component

ACCESSORIES

Trolley:

- To handle feeders
- Electrical/Pneumatic connections plate
- Storage box with four drawers
- Additional storage interface





+33 5 61 85 55 77

semo@semo.fr

10 rue Louis Breguet,

31700 Cornebarrieu, FRANCE



